

Bicycle Garage FULLERTON-PIN

The **FULLERTON-PIN** double-tier bicycle garage is the optimal solution for secure and convenient bike parking. Manufactured to the requirements of **DIN 79008**, our modular system guarantees the highest quality and durability. Featuring folded steel panels and a bicycle rail capable of accommodating tires up to 60 mm in width, it provides maximum stability and safety.

Our double-tier bicycle garage comes with numerous features for enhanced convenience, including charging options, storage compartments with grounded sockets and USB ports, as well as LED interior lighting for each compartment.

With a wide range of colors and design options, the garage can be customized to seamlessly integrate into its surroundings. The robust flat roof, galvanized side walls, and burglar-resistant door construction protect bicycles from weather exposure and unauthorized access.

The FULLERTON-PIN double-tier bicycle garage optimizes your parking space while creating a secure and organized environment. Experience its quality and functionality today!

Construction:

- Modular system available in single- or double-tier configuration, manufactured and certified according to **DIN 79008**
- Folded steel panels, 1.5 mm or 2.0 mm thick, bicycle entry rail with front wheel holder for tires up to 60 mm
- Double-tier version additionally equipped with extendable and tiltable bicycle entry rail, including backstop, wheel holder, and integrated gas spring to reduce effort; front wheel adjustment height 330 mm
- Charging option in the lower compartment including storage with grounded 230 V socket, 3 A circuit breaker, USB-A and USB-C, and LED interior lighting per compartment (optional, for additional cost)
- Version for recumbent and cargo bikes available on request

Surface / Color:

- All steel parts galvanized and powder-coated in ZIEGLER standard colors

Roof:

- Flat roof made of robust 1.5 mm steel, with internal reinforcement profiles

- Optional canopy and solar LED exterior lighting for double-tier version in anthracite, as well as roof greening tray (additional cost)

Rear, Intermediate, and Side Walls:

- Galvanized and profiled steel, 1.5 mm thick, with ventilation slots to prevent condensation and allow airflow
- Burglar-resistant, fastened internally with screws or rivets
- Optional side wall panels: perforated sheet, wooden cladding (spruce, glazed), aluminum strips with wood decor, or WPC in standard colors (additional cost)

Door:

- Robust, reinforced door frame made of 2 mm folded steel with vertical reinforcement bar
- Opening assistance via gas spring
- Includes coat/helmet hooks on the inside of the doors (for double-tier version, hooks only in lower compartments)
- Standard door hinge: DIN right
- Locking with PIN-code lock suitable for outdoor use (multi-user mode)
- Emergency unlocking via master code from outside, and internal emergency release
- Annual battery replacement recommended for uninterrupted operation
- Labeling and numbering available at extra cost
- Booking software available on request

Drainage:

- Free-draining over the rear roof edge

Installation:

- Adjustable feet for leveling on customer-supplied concrete slab according to our foundation plans (slab or strip foundation under feet)
- Includes floor fastening materials

Delivery:

- Single compartments pre-assembled at the factory
- Assembly instructions included
- Installation by our professional team is recommended and available on request